




AS-Interface CompactLine module

CompactM12 4 DI-Y V4A A/B



Application

Application

field installation

Electrical data

Operating voltage [V]

26.5...31.6 DC

Max. current consumption from AS-i [mA]

250

Inputs / outputs

Number of inputs and outputs

Number of digital inputs: 4

Inputs

Number of digital inputs

4

Input circuit of digital inputs

PNP; (type 2 according to IEC 61131-2)

Sensor supply of the inputs

AS-i

Power supply [V]

20...30; (DC)

Max. total current rating of inputs [mA]

200

Input current limitation [mA]

15



AS-Interface CompactLine module

CompactM12 4 DI-Y V4A A/B

Input current High	[mA]	6...10
Input current Low	[mA]	0...2
Switching level high	[V]	> 11
Digital inputs protected against short circuits		yes

Operating conditions

Ambient temperature	[°C]	-25...80
Storage temperature	[°C]	-25...80
Max. relative air humidity	[%]	90; (non condensing)
Max. height above sea level	[m]	2000
Protection		IP 67; (when flat cables are used E7400x / E7401x)

Tests / approvals

EMC	EN 61000-6-2	
	EN 62026-2	
	EN 50581	
MTTF	[years]	383
UL approval	power supply	Class 2

AS-i classification

AS-i version	2.11; 3.0				
AS-i addressing	IR addressing possible				
Extended addressing mode	yes				
AS-i master profile	M2; M3; M4				
AS-i profile	S-0.A.E				
AS-i I/O configuration	[hex]	0			
AS-i ID code	[hex]	A.E			
AS-i certificate	126701				
Assignment of the data bits	data bit	D0	D1	D2	D3
	input	1	2	3	4
	socket	I-1/2	I-1/2 / I-2	I-3/4	I-3/4 / I-4
	pin	4	2 4	4	2 4

Mechanical data

Weight	[g]	285.5
Housing		rectangular
Type of mounting		AS-i flat cables directly connectable; backplane mounting
Dimensions	[mm]	118.2 x 60 x 27
Materials		PA; socket: stainless steel (316L/1.4404); threaded inserts in the lower part: stainless steel (316L/1.4404); O-ring: EPDM; screws: stainless steel (316Cu/1.4578); piercing contacts: CuSn6 nickel-plated and tin-plated

Displays / operating elements

Display	switching status	LED, yellow I1...I4
	operation	LED, green AS-i
	errors	LED, red

Electrical connection

Module connection	Flat cables
-------------------	-------------




AS-Interface CompactLine module

CompactM12 4 DI-Y V4A A/B

Accessories	
Accessories (optional)	Stainless steel sleeve, for installation in case of high mechanical stress , E70402
Remarks	
Remarks	Do not connect any of the following points to an external potential: I-, I+, I1, I2, I3, I4 The connections are electrically connected with the AS-i cable.
Pack quantity	1 pcs.

Electrical connection

Connection



Connector: M12

	Inputs
1	Sensor supply +
2	data input
3	Sensor supply -
4	data input
5	functional earth (FE)