


AC1256



AS-Interface power supply

PSU-1AC/ASi-2,8A



1 LED AS-i ok



Application

Design

housing for DIN rail mounting

Electrical data

Frequency AC	[Hz]	47...64
Operating voltage tolerance	[%]	10
Operating voltage	[V]	automatic range selection
Nominal voltage AC	[V]	110 / 230
Input voltage range AC	[V]	100...120 / 200...240
Protection class		I
Overvoltage protection		yes; (< 36 V)
Max. power-on delay time	[ms]	900
Output voltage AS-i	[V]	30.5; (to PELV; NEC Class II)
Output power (permanent)	[W]	85
Power factor (nominal voltage 120 V AC / 60 Hz)		0.56
Power factor (nominal voltage 230 V AC / 50 Hz)		0.47
Number of output circuits		1
Output current AS-i	[A]	2.8
Max. residual ripple	[mV]	50



AS-Interface power supply

PSU-1AC/ASi-2,8A

Switch-on peak current (nominal voltage 120 V AC / 60 Hz)	[A]	3
Switch-on peak current (nominal voltage 230 V AC / 50 Hz)	[A]	3
Inrush current limitation		yes
Efficiency (nominal voltage 120 V AC / 60 Hz)	[%]	86.9
Efficiency (nominal voltage 230 V AC / 50 Hz)	[%]	88
External input protection		≤ B-10 A / ≤ C-6 A
Derating	[W/K]	0 (60...70 °C)
Mains buffering time (nominal voltage 120 V AC / 60 Hz)	[ms]	98
Mains buffering time (nominal voltage 230 V AC / 50 Hz)	[ms]	96
Input current (nominal voltage 120 V AC / 60 Hz)	[A]	1.44
Input current (nominal voltage 230 V AC / 50 Hz)	[A]	0.86
Power loss (nominal voltage 120 V AC / 60 Hz)	[W]	12.9
Power loss (nominal voltage 230 V AC / 50 Hz)	[W]	11.6
Integrated data decoupling		yes
Back feeding protection	[V]	35

Outputs

Short-circuit proof	yes
Overload protection	yes
Overload performance	output current constant
Parallel connection of outputs possible	no
Series connection of outputs possible	no

Operating conditions

Ambient temperature	[°C]	-25...70
Note on ambient temperature		observe the free space for convection (see operating instructions)
Storage temperature	[°C]	-40...85
Max. relative air humidity	[%]	95; (IEC 60068-2-30)
Protection		IP 20
Pollution degree		2; (IEC 62103: conductive soiling not permitted)

Tests / approvals


EMC	EN 61000-6-1	
	EN 61000-6-2	
	EN 61000-6-4	
Vibration resistance	IEC 60068-2-6	± 1,6 mm 2...17,8 Hz / 2 g 17,8...500 Hz
Shock resistance	IEC 60068-2-27	30 g 6 ms / 20 g 11 ms




AS-Interface power supply

PSU-1AC/ASi-2,8A

AS-i classification		
AS-i certificate	98701	
Mechanical data		
Weight	[g]	625
Housing	rectangular	
Type of mounting	mounting on DIN rail; (TH35 (EN 60715))	
Dimensions	[mm]	130.5 x 40 x 124.5
Materials	steel sheet	
Displays / operating elements		
Display	AS-i voltage	LED, green
Remarks		
Pack quantity	1 pcs.	
Electrical connection		
screw terminals:		
Connection		



- 1: primary
2: secondary






AS-Interface power supply

PSU-1AC/ASi-2,8A


output characteristics

Output Voltage




characteristic curve for degree of efficiency / power loss

Efficiency



characteristic line for derating

Allowed Output Current



characteristic line for mains buffering time

Hold-up Time

