



# i10-M0453 Lock

i10 Lock

SAFETY LOCKING DEVICES

**SICK**  
Sensor Intelligence.



actuator not supplied with delivery



### Ordering information

| Type           | part no. |
|----------------|----------|
| i10-M0453 Lock | 6029934  |

Other models and accessories → [www.sick.com/i10\\_Lock](http://www.sick.com/i10_Lock)

### Detailed technical data

#### Features

|                                                         |                        |
|---------------------------------------------------------|------------------------|
| <b>Sensor principle</b>                                 | Electro-mechanical     |
| <b>Locking principle</b>                                | Power to release       |
| <b>Positive action N/C solenoid monitoring contacts</b> | 2                      |
| <b>N/O solenoid monitoring contacts</b>                 | 0                      |
| <b>Positive action N/C door monitoring contacts</b>     | 2                      |
| <b>N/O door monitoring contacts</b>                     | 0                      |
| <b>N/C contact for door monitoring</b>                  | 0                      |
| <b>Locking force <math>F_{max}</math></b>               | 1,300 N (EN ISO 14119) |
| <b>Locking force <math>F_{Zh}</math></b>                | 1,000 N (EN ISO 14119) |
| <b>Actuation force</b>                                  | $\geq 10$ N            |
| <b>Retaining force</b>                                  | $\leq 20$ N            |
| <b>Actuation frequency</b>                              | $\leq 1,200$ /h        |
| <b>Actuation directions</b>                             | 4                      |
| <b>Approach speed</b>                                   | $\leq 20$ m/min        |

#### Safety-related parameters

|                                           |                                                                                                                                                                                   |
|-------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b><math>B_{10d}</math> parameter</b>     | $3 \times 10^6$ switching cycles (with small load)                                                                                                                                |
| <b>Type</b>                               | Type 2 (EN ISO 14119)                                                                                                                                                             |
| <b>Actuator coding level</b>              | Low coding level (EN ISO 14119)                                                                                                                                                   |
| <b>Safe state in the event of a fault</b> | The switch has no internal fault detection and is unable to assume a safe state in the event of a fault. Fault detection is performed by the connected safety-related logic unit. |

#### Functions

|                               |                                                 |
|-------------------------------|-------------------------------------------------|
| <b>Safe series connection</b> | None, only individual wiring (with diagnostics) |
|-------------------------------|-------------------------------------------------|

## Interfaces

|                         |                                              |
|-------------------------|----------------------------------------------|
| <b>Connection type</b>  | Cable gland, 3 x M20                         |
| Conductor cross section | 0.34 mm <sup>2</sup> ... 1.5 mm <sup>2</sup> |

## Electronics

|                                                        |                                 |
|--------------------------------------------------------|---------------------------------|
| <b>Contamination rating</b>                            | 3                               |
| <b>Switching principle</b>                             | Slow action switching element   |
| <b>Usage category</b>                                  | AC-15/DC-13 (IEC 60947-5-1)     |
| <b>Rated operating current (voltage)</b>               | 4 A (230 V AC)<br>4 A (24 V DC) |
| <b>Rated insulation voltage U<sub>i</sub></b>          | 250 V                           |
| <b>Rated impulse withstand voltage U<sub>imp</sub></b> | 2,500 V                         |
| <b>Type of output</b>                                  | Electro-mechanical contacts     |
| <b>Power consumption</b>                               | ≤ 8 W                           |
| <b>Short-circuit protection</b>                        | 4 A gG                          |
| <b>Switching voltage</b>                               | ≥ 12 V DC                       |
| <b>Switching current (switching voltage)</b>           | 1 mA (24 V DC)                  |
| <b>Solenoid operating voltage</b>                      | (20.4 V DC ... 26.4 V DC)       |
| <b>Switch-on time of magnet</b>                        | 100 %                           |
| <b>Locking principle</b>                               | Power to release                |

## Mechanics

|                         |                                      |
|-------------------------|--------------------------------------|
| <b>Weight</b>           | 0.46 kg                              |
| <b>Housing material</b> | Glass-fiber reinforced thermoplastic |
| <b>Mechanical life</b>  | 1 x 10 <sup>6</sup> switching cycles |

## Ambient data

|                                      |                   |
|--------------------------------------|-------------------|
| <b>Enclosure rating</b>              | IP67 (IEC 60529)  |
| <b>Ambient operating temperature</b> | -20 °C ... +55 °C |
| <b>Storage temperature</b>           | -20 °C ... +55 °C |


## Certificates

|                                     |   |
|-------------------------------------|---|
| <b>EU declaration of conformity</b> | ✓ |
| <b>UK declaration of conformity</b> | ✓ |
| <b>China-RoHS</b>                   | ✓ |
| <b>cULus certificate</b>            | ✓ |

## Classifications




|                     |          |
|---------------------|----------|
| <b>ECLASS 5.0</b>   | 27272603 |
| <b>ECLASS 5.1.4</b> | 27272603 |
| <b>ECLASS 6.0</b>   | 27272603 |
| <b>ECLASS 6.2</b>   | 27272603 |
| <b>ECLASS 7.0</b>   | 27272603 |
| <b>ECLASS 8.0</b>   | 27272603 |
| <b>ECLASS 8.1</b>   | 27272603 |

## Dimensional drawing



Dimensions in mm (inch)

## Switching elements

|                      | Actuator inserted                                                                                                                                            |                                                                                                                                                              | Actuator removed                                                                                                                                             |
|----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                      | locked                                                                                                                                                       | unlocked                                                                                                                                                     |                                                                                                                                                              |
|                      |                                                                             |                                                                             |                                                                             |
| Switching element 23 | $\begin{matrix} \updownarrow 41 \text{ N/C } 42 \\ 33 \text{ N/O } 34 \\ \updownarrow 21 \text{ N/C } 22 \\ 11 \text{ N/C } 12 \end{matrix}$                 | $\begin{matrix} \updownarrow 41 \text{ N/C } 42 \\ 33 \text{ N/O } 34 \\ \updownarrow 21 \text{ N/C } 22 \\ 11 \text{ N/C } 12 \end{matrix}$                 | $\begin{matrix} \updownarrow 41 \text{ N/C } 42 \\ 33 \text{ N/O } 34 \\ \updownarrow 21 \text{ N/C } 22 \\ 11 \text{ N/C } 12 \end{matrix}$                 |
| Switching element 25 | $\begin{matrix} \updownarrow 41 \text{ N/C } 42 \\ 31 \text{ N/C } 32 \\ \updownarrow 21 \text{ N/C } 22 \\ 13 \text{ N/O } 14 \end{matrix}$                 | $\begin{matrix} \updownarrow 41 \text{ N/C } 42 \\ 31 \text{ N/C } 32 \\ \updownarrow 21 \text{ N/C } 22 \\ 13 \text{ N/O } 14 \end{matrix}$                 | $\begin{matrix} \updownarrow 41 \text{ N/C } 42 \\ 31 \text{ N/C } 32 \\ \updownarrow 21 \text{ N/C } 22 \\ 13 \text{ N/O } 14 \end{matrix}$                 |
| Switching element 31 | $\begin{matrix} \updownarrow 41 \text{ N/C } 42 \\ \ominus 31 \text{ N/C } 32 \\ \updownarrow 21 \text{ N/C } 22 \\ 13 \text{ N/O } 14 \end{matrix}$         | $\begin{matrix} \updownarrow 41 \text{ N/C } 42 \\ \ominus 31 \text{ N/C } 32 \\ \updownarrow 21 \text{ N/C } 22 \\ 13 \text{ N/O } 14 \end{matrix}$         | $\begin{matrix} \updownarrow 41 \text{ N/C } 42 \\ \ominus 31 \text{ N/C } 32 \\ \updownarrow 21 \text{ N/C } 22 \\ 13 \text{ N/O } 14 \end{matrix}$         |
| Switching element 45 | $\begin{matrix} \updownarrow 41 \text{ N/C } 42 \\ \ominus 31 \text{ N/C } 32 \\ \updownarrow 21 \text{ N/C } 22 \\ \ominus 11 \text{ N/C } 12 \end{matrix}$ | $\begin{matrix} \updownarrow 41 \text{ N/C } 42 \\ \ominus 31 \text{ N/C } 32 \\ \updownarrow 21 \text{ N/C } 22 \\ \ominus 11 \text{ N/C } 12 \end{matrix}$ | $\begin{matrix} \updownarrow 41 \text{ N/C } 42 \\ \ominus 31 \text{ N/C } 32 \\ \updownarrow 21 \text{ N/C } 22 \\ \ominus 11 \text{ N/C } 12 \end{matrix}$ |

$\updownarrow$  Positive action N/C locking monitoring contact  
 $\ominus$  Positive action N/C door monitoring contact

**Switching element 23:**  
 2 positive action N/C contacts + 1 N/O contact (Locking monitoring)  
 1 N/C contact (Door monitoring)

**Switching element 25:**  
 2 positive action N/C contacts (Locking monitoring)  
 1 N/C contact + 1 N/O contact (Door monitoring)

**Switching element 31:**  
 2 positive action N/C contacts (Locking monitoring)  
 1 positive action N/C + 1 N/O contact (Door monitoring)

**Switching element 45:**  
 2 positive action N/C contacts (Locking monitoring)  
 2 positive action N/C contacts (Door monitoring)

## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

**For us, that is “Sensor Intelligence.”**

## WORLDWIDE PRESENCE:

Contacts and other locations –[www.sick.com](http://www.sick.com)