

1) not included in scope of delivery, 2) Housing length, 3) Recommended bracket distance, 4) Null point, 5) Nominal length, 6) Mechanical null point, 7) Stroke



### Basic features

Approval/Conformity	CE UKCA cULus WEEE
Generation	1
Principle of operation	Inductive positioning system
Version	Version P1

### Display/Operation

Setting	Output curve rising/falling
---------	-----------------------------

### Electrical connection

Connection	M12x1, 8-pin
Connection version	axial
Polarity reversal protected	to 36 V
Short-circuit protection	to GND and to 36 V DC

### Electrical data

Current consumption max. at 24 V DC	90 mA
Galvanic isolation	yes
Inrush current	≤ 3 A/0.5 ms
Operating voltage $U_b$	18...30 VDC
Output current max.	6 mA
Output signal adjustable	using programming inputs
Overvoltage protection	to 36 V
Repeat accuracy absolute	10 $\mu$ m
Residual ripple max.	0.5 Vpp
Switch-on delay max.	500 ms
Voltage-proof up to (GND to housing)	500 V DC

### Environmental conditions

Ambient temperature	-20...85 °C
EN 60068-2-27, Shock	100 g, 6 ms
EN 60068-2-6, Vibration	12 g, 10...2000 Hz
IP rating	IP54, with connector
Storage temperature	-40...100 °C

### Functional safety

MTTF (40 °C)	77 a
--------------	------

### Interface

Analog output	Analog, voltage 0...10 V
Bracket distance, recommended	55 mm
Output characteristic	linear rising/falling

### Material

Cover material	Zinc, Die-cast, nickel plated
Housing material	Aluminium, Anodized


### Mechanical data

Housing length	175 mm
Hub	85 mm
Mounting part	Mounting clamps
Tightening torque max.	2 Nm

### Range/Distance

Measuring range	75 mm
Nominal length	75 mm
Non-linearity max.	±15 µm
Repeatability	≤10 µm
Resolution	≤ 0.15 mV
Sampling rate typ.	32 kHz
Traverse speed max.	7 m/s

## Connector Drawings



## Wiring Diagrams (Schematic)

Pin	
1	Lb
2	0 V
3	NC
4	La
5	0...10 V
6	GND
7	+24V DC
8	NC