



BTL abcdef-nnnn-ghijklmo-pqrstu

BTL

Magnetostrictive linear position sensor

a Mounting

P = Profile

b Housing geometry

P = Profile 35x36,8 mm, Aluminium, axial

c Detailed design 1

0 = without mounting brackets

5 = with mounting brackets profile 5: BAM MC-TL-025-P-1

d Detailed design 2

4 = zero point= 67 mm

ef Special design feature

00 = none

nnnn Measuring range

0500 = Specification in mm

(0025 ... 5000)

g Performance class

C = Platform Basic, Level 2

h Version Performance class

1

i Supply voltage

2 = 18 ... 30 V

j Interface group

N = Networking

k Interface type

E = EtherCAT

l Characteristic Interface 1

1 = 1 magnet fix

2 = 2 magnets fix

3 = 1 magnet + velocity (fixed)

4 = 2 magnets fix

5 = 1-4 magnets (flexible)

m Characteristic Interface 2

0 = none

o Characteristic Interface 3

0 = none

p Cable/leads

0 = without cable/leads

qr Cable length

00 = without cable/leads

s Connector type

C = Multi-plug

tu Connector model

05 = Multiple (M12 4 pole, M8 4 pole)

Basic features

Approval/Conformity	CE UKCA cULus WEEE
Magnets, number (factory setting)	l = 1, 3: 1 l = 2: 2 l = 4, 5: 4
Magnets, number max.	l = 1, 3: 1 l = 2: 2 minimum separation between magnets 65 mm. l = 4, 5: 4 minimum separation between magnets 65 mm.

Electrical connection

Polarity reversal protected	Ub up to 36 V
Short-circuit protection	Signal output against GND

Electrical data

Current consumption max. at 24 V DC	70 mA
Error value	0x7FFFFFFF
Inrush current	≤ 3 A/0.5 ms
Operating voltage Ub	18...30 VDC
Overvoltage protection	Ub up to 36 V DC
Switch-on delay max.	10 s
Voltage-proof up to (GND to housing)	500 V DC

Environmental conditions

Ambient temperature	-25...85 °C
EN 55016-2-3, Radiation	For industrial and residential use
EN 60068-2-27, Continuous shock	50 g, 2 ms
EN 60068-2-27, Shock	100 g, 6 ms
EN 60068-2-6, Vibration	12 g, 10...2000 Hz
EN 61000-4-2, ESD	Severity Level 3
EN 61000-4-3, RFI	Severity Level 3
EN 61000-4-4, Burst	Severity Level 3
EN 61000-4-5, Surge	Severity Level 2
EN 61000-4-6, High-frequency fields	Severity Level 3
EN 61000-4-8 Magnetic fields	Severity Level 4
IP rating	IP67 with connector
Relative humidity	≤ 90 %, non-condensing
Storage temperature	-25...100 °C
Temperature coefficient typ.	≤ 30 ppm/K at 50% of nominal stroke 500mm

Functional safety

MTTF (40 °C)	196 a
--------------	-------

Interface

Data format	32-bit signed
Interface	EtherCAT
Process data, Master – Device	0 bytes
Prozess data, Device – Master	l = 1: 7 Byte l = 2,3: 11 Byte l = 4,5: 19 Byte

Material

Cover material	Zinc, Die casting
Housing material	Aluminium, Anodized
Housing material, surface protection	Anodized

Mechanical data

Overall Length	nnnn + 137 mm
Speed detectable max.	10 m/s

Range/Distance

Linearity deviation	± 50 µm
Measuring length	25...5000 mm
Null point	67 mm
Repeat accuracy	≤ ± 10 µm
Resolution, position	1 µm
Sampling frequency max.	nnnn = 25...500: 2000 Hz nnnn = 501...1270: 1000 Hz nnnn = 1271...2650: 500 Hz nnnn = 2651...5000: 250 Hz

