



BTL6-abcd-Mnnnn-f-lm

BTL6

Magnetostrictive linear position sensor Generation 6

a Interface

V = EtherNet

b Operating voltage

5 = 10 ... 30 V

c Interface characteristic 1

1 = Device profile length measuring systems
5 = Device Profile EUROMAP 75

d Interface characteristic 2

V = Varan

Mnnnn Nominal length (4-position)

M0500 = metric in mm
(M0050...M4572)

f Form factor

PF = Flat profile

l Connection type

S = Connector

m Connection type characteristic 1

115 = M12x1 connector with 8 pins

Basic features

Approval/Conformity	CE UKCA cULus WEEE
Magnets, number (factory setting)	1
Magnets, number max.	2 minimum separation between magnets 65 mm.

Display/Operation

Error value	0x7FFFFFFF
-------------	------------

Electrical connection

Polarity reversal protected	Ub up to 36 V
Short-circuit protection	to GND

Electrical data

Current consumption max. at 24 V DC	80 mA
Inrush current	≤ 4A / 0.5ms
Operating voltage Ub	10...30 VDC
Output signal adjustable	no
Overvoltage protection	Ub up to 36 V
Switch-on delay max.	4 s
Voltage-proof up to (GND to housing)	500 V DC

Environmental conditions

Ambient temperature	0...85 °C
EN 55016-2-3, Radiation	For industrial and residential use
EN 60068-2-27, Continuous shock	50 g, 2 ms
EN 60068-2-27, Shock	50 g, 6 ms
EN 60068-2-6, Vibration	12 g, 10...2000 Hz
EN 61000-4-2, ESD	Severity Level 3
EN 61000-4-3, RFI	Severity Level 3
EN 61000-4-4, Burst	Severity Level 3
EN 61000-4-5, Surge	Severity Level 2
EN 61000-4-6, High-frequency fields	Severity Level 3
EN 61000-4-8 Magnetic fields	Severity Level 4
IP rating	IP67 with connector
Relative humidity	≤ 90 %, non-condensing
Storage temperature	-40...100 °C
Temperature coefficient typ.	≤ 20 ppm/K at 50% of nominal stroke 500mm

Functional safety

MTTF (40 °C)	138 a
--------------	-------

Interface

Data format	32-bit signed
Interface	Varan

Material

Cover material	Zinc, Die casting
Housing material	Aluminium, Anodized
Housing material, surface protection	Anodized


Mechanical data

Overall Length	nnnn + 146 mm
Speed detectable max.	10 m/s

Range/Distance


Linearity deviation	nnnn = 0050...0500: ± 150 µm nnnn > 0500: ± 0.03% FS
Measuring length	50...4572 mm
Repeat accuracy	≤ 10 µm
Resolution, position	2.5 µm
Sampling frequency max.	See illustration for measuring frequency

Characteristic Diagram




1) 1 magnet
2) 2 magnets
x: Nominal length [mm]
y: fA,max Hz

BTL6-V55V-Mxxxx-PF-S115



1) not included in scope of delivery
2) Non-usable area
3) Nominal length = Measuring length
4) Null point
5) Overall length
6) LED function indicator

BTL6-V51V-Mxxxx-PF-S115



- 1) not included in scope of delivery
- 2) Non-usable area
- 3) Nominal length = Measuring length
- 4) Null point
- 5) Overall length
- 6) LED function indicator